

**In the Claims:**

Claim 1. (Currently amended) A system for monitoring a patient, comprising:  
vibration ~~sensing means~~ sensor for collecting tracheal vibration information from the patient; and  
position ~~sensing means~~ sensor that changes state depending upon its orientation with respect to the earth's gravity, at least a portion of which is substantially adjacent to a portion of the vibration ~~sensing means~~ sensor.

Claim 2. (Currently amended) The system of claim 1, wherein the vibration ~~sensing means~~ sensor comprises a microphone.

Claim 3. (Currently amended) The system of claim 1, wherein the position ~~sensing means~~ sensor comprises an accelerometer.

Claim 4. (Currently amended) The system of claim 1, wherein the position ~~sensing means~~ sensor comprises a gravity sensing switch having at least one axis of orientation with respect to gravity such that the switch occupies different states depending upon which end of the axis is closer to the source of gravity.

Claim 5. (Currently amended) The system of claim 4, wherein the gravity sensing switch further comprises a tilt switch having:

a body containing a cavity;

a plurality of contact point pairs within the cavity;

an electrically conductive material that is able to move within the cavity, such that as the orientation of the body with respect to gravity changes different pairs of contact

points are ~~connected~~ coupled, thus providing a signal indicative of the tilt switch's orientation with respect to gravity.

Claim 6. (Currently amended) The system of claim 4, wherein the position ~~sensing means~~ sensor comprises:

a first gravity sensing switch having a first axis of orientation with respect to gravity; and

a second gravity sensing switch having a second axis of orientation with respect to gravity which can be ~~superpositioned~~ superposed at an angle to the first axis.

Claim 7. (Currently amended) The system of claim 6, further comprising a means for coupling at least a portion of the system to at least a portion of the patient's body, such that the position ~~sensing means~~ sensor provides information indicative of changes in orientation of the portion of the patient's body to which the system is adapted to be coupled.

Claim 8. (Currently amended) The system of claim 7, wherein a plane containing ~~the superposition of the two axes~~ a superposition of the first axis and the second axis is at an angle to the portion of the patient's body to which the system is adapted to be coupled such that the position ~~sensing means~~ sensor provides information indicative of which of two or more positions the portion of the patient's body is in with respect to the earth's gravity.

Claim 9. (Currently amended) The system of claim 8, wherein the portion of the patient's body to which ~~the housing~~ a portion of the system is adapted to be coupled, and to which the plane is at an angle, is an axial portion.

Claim 10. (Currently amended) The system of claim 9, wherein the angle between the two ~~superpositioned~~ superposed axes is substantially a right angle.

Claim 11. (Original) The system of claim 10, wherein the angle between the plane and the axial portion of the patient's body is substantially a right angle.

Claim 12. (Currently amended) The system of claim 1, further comprising means for simultaneously coupling at least a portion of the vibration ~~sensing-means~~ sensor and a portion of the position ~~sensing-means~~ sensor to a portion of the patient's body, such that the position ~~sensing-means~~ sensor tracks changes in orientation of the portion of the patient's body to which the system is adapted to be coupled.

Claim 13. (Currently amended) The system of claim 12, wherein the means for simultaneously coupling further comprises a housing containing at least a portion of the vibration ~~sensing-means~~ sensor and a portion of the position ~~sensing-means~~ sensor.

Claim 14. (Original) The system of claim 13, wherein the means for simultaneously coupling further comprises an adhesive material coupled to a portion of the housing.

Claim 15. (Currently amended) The system of claim 9, wherein the angle between the ~~superpositioned~~ superposed axes of the two ~~tilt~~ gravity sensing switches, and the angle between the plane and the axial portion of the patient's body~~[[,]]~~ are such that the ~~tilt~~ gravity sensing switches indicate which of two or more positions the axial portion of the patient's body is in, one of which positions is substantially supine and one of which positions is not substantially supine.

Claim 16. (Currently amended) The system of claim 9, wherein the angle between the ~~superpositioned~~ superposed axes of the two ~~tilt~~ gravity sensing switches, and the angle between the plane and axial portion of the patient's body~~[[,]]~~ are such that the ~~sensor indicates~~ gravity sensing switches provide information indicative of which of four or more positions the axial portions of the patient's body is in, one of which positions is substantially supine, one of which positions is substantially prone, one of which positions is substantially left lateral decubitus, and one of which positions is substantially right lateral decubitus.

Claim 17. (Currently amended) The system of claim 4, further comprising means for coupling the system to an axial portion of the patient's body, with the axis of the ~~tilt~~ gravity sensing switch at an angle to the axial portion such that the ~~tilt~~ gravity sensing switch provides information indicative of which of two or more positions the axial portion of the patient's body is in, one of which positions is substantially supine and one of which positions is not substantially supine.

Claim 18. (Currently amended) The system of claim 1, further comprising a recording means for recording data representing the tracheal vibration information and data representing the state of the position ~~sensing means~~ sensor over time.

Claim 19. (Original) The system of claim 13, further comprising a recording means for recording data representing the tracheal vibration information and data indicative of the orientation of the portion of the patient's body to which the system is coupled over time.

Claim 20. (Original) The system of claim 19, further comprising a sampling means capable of sampling the tracheal vibration information at a rate of at least 2 kilohertz.

Claim 21. (Original) The system of claim 19, wherein the recording means further comprises:

a memory;

a power source,

conversion means for receiving the tracheal vibration information and the information indicative of the orientation of the patient's body and converting them into digital data; and

means for writing the digital data into the memory.

Claim 22. (Original) The system of claim 21, wherein the memory further comprises a memory capable of storing 32 megabytes of data.

Claim 23. (Currently amended) The system of claim 21, wherein an input of the conversion means is ~~connected~~ coupled to an output of at least one of the ~~sensing means~~ sensor by a wireless transmitter and receiver, where the transmitter is ~~connected~~ coupled to an output of the ~~sensing means~~ sensor and the receiver is ~~connected~~ coupled to an input of the conversion means.

Claim 24. (Currently amended) The system of claim 21, wherein an output of the conversion means is ~~connected~~ coupled to an input of the memory by a wireless transmitter and receiver, where the transmitter is ~~connected~~ coupled to the output of the conversion means and the receiver is ~~connected~~ coupled to an input of the memory.

Claim 25. (Original) The system of claim 21, further comprising a playback means capable of substantially recreating the collected tracheal vibration information from the recording means.

Claim 26. (Currently amended) The system of claim 25, wherein the vibration ~~sensing means~~ sensor further comprises a microphone having a frequency response of at least approximately 400 to 1000 hertz, and the playback means further comprises a sound output device capable of reproducing sound in a range of at least approximately 400 to 1000 hertz, such that upon playback of the data representing the collected tracheal vibration information a listener hears at least substantially the same sound that the listener would have heard through a listening device having a frequency response of at least approximately 400 to 1000 hertz in the same position as the vibration ~~sensing means~~ sensor at the time the tracheal vibration information was collected.

Claim 27. (Currently amended) The system of claim 25, wherein the vibration ~~sensing means~~ sensor further comprises a microphone having a frequency response, and the playback means further comprises a sound output device capable of reproducing sound in a range of at least approximately the same frequency response as the microphone, such that upon playback of the data representing the collected tracheal vibration information a listener hears at least substantially the same sound that the listener would have heard through a listening device having approximately the same frequency response as the microphone in the same position as the microphone at the time the tracheal vibration information was collected.

Claim 28. (Currently amended) The system of claim 25, wherein the vibration ~~sensing means~~ sensor further comprises a microphone having a frequency response containing a portion of the range of 400 to 1000 hertz, and the playback means further comprises a sound output device capable of reproducing sound in the same portion of the range of 400 to 1000 hertz, such that upon playback of the data representing the collected tracheal information a listener hears at least substantially the same sound that the listener would have heard at the time the tracheal vibration information was collected through a listening device having approximately the same frequency response as the microphone in a peri-tracheal position on the patient.

Claim 29. (Original) The system of claim 19, further comprising a computing device for reading and performing calculations on the recorded data.

Claim 30. (Original) The system of claim 13, further comprising an indicator means on the housing for showing the orientation the housing is to have when coupled to the patient's body.

Claim 31. (Original) A method for monitoring a patient, comprising:  
collecting tracheal vibration information from the patient at a location on the patient's body; and  
obtaining information indicative of the orientation of a portion of the patient's body with respect to gravity substantially adjacent to the location at which the tracheal vibration information is collected.

Claim 32. (Currently amended) A method for monitoring a patient, comprising:

coupling to the patient a vibration ~~sensing-means~~ sensor for collecting tracheal vibration information from a patient; and

coupling to at least a portion of the patient's body, substantially adjacent to the vibration ~~sensing-means~~ sensor, a position ~~sensing-means~~ sensor that changes state depending upon its orientation with respect to gravity, such that the position ~~sensing-means~~ sensor provides information that is indicative of the orientation with respect to gravity of the portion of the patient's body to which it is coupled.

Claim 33. (Original) The method of claim 32, further comprising the step of recording data representing tracheal vibration information and information indicative of the orientation of the portion of the patient's body that are obtained over time.

Claim 34. (Currently amended) The method of claim 33, wherein the step of recording data further comprises recording data from both the vibration ~~sensing-means~~ sensor and the position ~~sensing-means~~ sensor that are obtained concurrently.

Claim 35. (Original) The method of claim 33, wherein the step of recording data further comprises recording data during a period of time associated with diminished consciousness of the patient.

Claim 36. (Currently amended) The method of claim 32, wherein the step of coupling a vibration ~~sensing-means~~ sensor further comprises coupling a microphone to the patient.



Claim 37. (Currently amended) The method of claim 32, wherein the step of coupling to the patient a vibration ~~sensing means~~ sensor further comprises coupling said means near a tracheal segment of the patient.

Claim 38. (Currently amended) The method of claim 32, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling an accelerometer.

Claim 39. (Currently amended) The method of claim 32, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling to a portion of the patient's body a gravity sensing device having at least one axis of orientation with respect to gravity such that the gravity sensing device occupies different states depending upon which end of the axis is closer to the source of gravity.

Claim 40. (Original) The method of claim 39, wherein the gravity sensing device is coupled to an axial portion of the patient's body with the axis of orientation of the gravity sensing device at an angle to the axial portion such that the gravity sensing device provides information indicative of which of two or more positions the axial portion of the patient's body is in, one of which positions is substantially supine and one of which positions is not substantially supine.

Claim 41. (Currently amended) The method of claim 39, wherein step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling:

a first gravity sensing device having a first axis of orientation with respect to gravity; and

a second gravity sensing device having a second axis of orientation with respect to gravity which can be ~~superpositioned~~ superposed at an angle to the first axis.

Claim 42. (Currently amended) The method of claim 41, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling the gravity sensing devices to an axial portion of the patient's body with a plane containing ~~the~~ a superposition of the two axes at an angle to an axial portion of the patient's body such that the states of the gravity sensing devices provide information indicative of which of two or more positions the axial portion of the patient's body is in.

Claim 43. (Currently amended) The method of claim 41, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling the gravity sensing devices to an axial portion of the patient's body with the angle between the superposition of the two axes, and the angle between the plane containing the gravity sensing devices and the axial portion of the patient's body, being such that the states of the gravity sensing devices provide information indicative of which of two or more positions the axial portion of the patient's body is in, one of which positions is substantially supine and one of which positions is not substantially supine.

Claim 44. (Currently amended) The method of claim 41, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling the gravity sensing devices to an axial portion of the patient's body with the angle between the axes of the two gravity sensing devices, and the angle between the plane containing the gravity sensing devices and long axis of the patient's body, being such that the states of the gravity sensing devices provide information indicative of which of three or more

positions the axial portion of the patient's body is in, one of which positions is substantially supine, one of which positions is substantially prone, and one of which positions is one or more of the substantially lateral decubitus positions of the patient.

Claim 45. (Currently amended) The method of claim 41, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling the gravity sensing devices to an axial portion of the patient's body with the angle between the ~~superpositioned~~ superposed axes of the two gravity sensing devices, and the angle between the plane and axial portion of the patient's body, being such that the states of the gravity sensing devices provide information indicative of which of four or more positions the axial portion of the patient's body is in, one of which positions is substantially supine, one of which positions is substantially prone, one of which positions is left lateral decubitus, and one of which positions is right lateral decubitus.

Claim 46. (Currently amended) The method of claim 41, wherein the step of coupling a position ~~sensing means~~ sensor to the patient further comprises coupling to the patient a housing containing the vibration ~~sensing means~~ sensor and the first and second gravity sensing devices.

Claim 47. (Currently amended) The method of claim 41, wherein the first gravity sensing device further comprises a tilt switch having:

- a body containing a cavity;
- a plurality of contact point pairs within the cavity;
- an electrically conductive material that is able to move within the cavity, such that as the orientation of the body with respect to gravity changes different pairs of contact

points are ~~connected~~ coupled, thus providing a signal indicative of the switch's orientation with respect to gravity. [[.]]

Claim 48. (Original) The method of claim 41, wherein the first gravity sensing device is an accelerometer.

Claim 49. (Original) The method of claim 34, wherein the step of recording data representing the tracheal vibration and orientation information further comprises the steps of:

providing a memory;  
converting the tracheal vibration information and information indicative of the orientation of the portion of the patient's body into digital data; and  
writing the digital data into the memory.

Claim 50. (Original) The method of claim 49, wherein the step of providing a memory further comprises providing a non-volatile memory, and further comprises the step of:

coupling the non-volatile memory to the patient such that the patient may be in a state of diminished consciousness without being disturbed during the period of diminished consciousness.

Claim 51. (Currently amended) The method of claim 49, wherein the step of recording data further comprises the step of:

wirelessly transmitting the tracheal vibration information and information indicative of the orientation of the portion of the patient's body from the ~~sensing means~~

sensor to a recording device containing a memory before the step of converting the data into digital data.

Claim 52. (Original) The method of claim 49, wherein the step of recording data further comprises the step of:

wirelessly transmitting the digital data to a recording device containing a memory between the steps of converting the information into digital data and the step of writing the digital data into the memory.